Disassembly and Recycling Document

Disassembly Time: 10min / No Special Training Required


Model: Brooks

*Refer to P.2 for model variations

Tools Required

safetly glasses mallet phillips screwdriver prybar/flathead screwdriver






Breakdown Steps

- Use a mallet to tap on the bottom of plastic seat back. Seat back should slide up and off of screws (figure A).
 After the back is removed, use a screw driver to unscrew the shoulder screws from the back.
- 2. Turn chair frame on its side to reveal leg cap glides inserted into the bottom of the leg. To remove, use a pair of vice grips to clamp onto the revealed plastic. Use a mallet to tap the cap guide out of the chair leg (figure B). Repeat for each leg.
- Keeping the seat upside down, use a pry bar to remove the seat pan from the bottom of the frame (figure C). Seat pan should pop out relatively easily.
- To remove the seat, keep the frame upside down and unscrew the four screws holding the seat in place (figure D).













Disassembly and Recycling DocumentDisassembly Time: 10min / No Special Training Required

Chair Variations

Brooks

All versions of the brooks chair have the option of having no arms or having arms. All other variations are with material use.

- Fully upholstered seat and back cast aluminum arms(figure A1).
- HDPE seat and back with nylon arms (figure A2).
- Plywood seat and back with no arms (figure A3).

Disassembly for all of these versions is the same as the original. Please use P1 as a disassembly reference for all of these variations.





